



US005986337A

United States Patent [19]**Takagi et al.****[11] Patent Number: 5,986,337****[45] Date of Patent: Nov. 16, 1999**

[54] **SEMICONDUCTOR ELEMENT MODULE
AND SEMICONDUCTOR DEVICE WHICH
PREVENTS SHORT CIRCUITING**

[75] Inventors: **Shinichi Takagi; Akinobu Suzuki,**
both of Tokyo, Japan

[73] Assignee: **Mitsubishi Denki Kabushiki Kaisha,**
Tokyo, Japan

[21] Appl. No.: **09/138,562**

[22] Filed: **Aug. 24, 1998**

[30] **Foreign Application Priority Data**

Nov. 17, 1997 [JP] Japan 9-315260

[51] **Int. Cl.⁶ H01L 23/48**

[52] **U.S. Cl. 257/693; 257/697; 257/730;
257/692**

[58] **Field of Search 257/697, 692,
257/693, 698, 730**

[56] **References Cited**

U.S. PATENT DOCUMENTS

4,868,638 9/1989 Hirata et al. .
5,398,165 3/1995 Niinou .
5,567,984 10/1996 Zalesinski et al. .

FOREIGN PATENT DOCUMENTS

62-163347 7/1987 Japan 257/697

63-174344	7/1988	Japan	257/697
1-39051	2/1989	Japan	257/697
1-60542	4/1989	Japan	
2-29538	2/1990	Japan	
4-146652	5/1992	Japan	
4-199556	7/1992	Japan	257/697
5-102348	4/1993	Japan	257/693
5-144962	6/1993	Japan	257/697

OTHER PUBLICATIONS

Article issued by Ohm, "Handbook for Electronics and Communication Engineers," *Electric-Communication Hand Book*, dated Mar. 30, 1979, cover pages, and p. 577.

Primary Examiner—Sheila V. Clark
Attorney, Agent, or Firm—Burns, Doane, Swecker & Mathis, LLP

[57] ABSTRACT

A semiconductor element module includes a package, a semiconductor element arranged on the package, and a plurality of leads provided on sides of the package so that an opening end of each the lead is oriented to the side of a package attaching plane, and serving to connect the semiconductor element to an external circuit; wherein a level difference is provided on the side of the package attaching plane of each of package sides so that a space is formed from each the plurality of leads.

10 Claims, 6 Drawing Sheets